



Watt



Range (Up to)



Operation **Time**



Front Dia

LED bulb life

NET Weight

Gross Weight

Circuitry

Handle



Modes



Weight





Optionally Available with Car Adapter

Specifications

Type of lamp/Wattage Dia of search light (Approx) Dimensions.

Box Dimensions Solar Panel

Color temperature (Degree k) Type of battery (Rechargeable) Type/Color of housing material **Continuous operation time**

(High/Low Mode)

Battery Charging Time

Charging

Battery Level Indicator Charging Indicator

Full Charge Indicator

Range

Op RH

Operation Modes Op Temp Range

LED/15 W 105 mm

210 X 105 X 148 mm 230 X 125 X 130 mm.

Inbuilt 6500K

3X18650 (6000mAh) Li-ion Battery Pack

ABS/Black

12/18 (Hours Approx)

8 hours (Approx)

AC Mains 220V50Hz/Inbuilt Solar Panel

25%-50%-75%-100% **Provided. Turns Red**

Provided. Turns Green from Red

Up to 1Km Approx

6 Modes (Low-Medium-High-SOS-Flasher-Work Light)

-10 deg C to +55 deg C.

95%



Up to 1,00,000 hrs.

(Including Battery)

415 gms Approx

590 gms Approx

IC based & compact.