



LED Revolving Search Lights

Auto/Semi Automatic Variants

Model: YK-REVO SR Series

YK-REVO 150 SR / 200 SR / 250 SR / 300 SR

**300
W**

Watt
(Model Specific)

**1
KM**

Range (Up to)
(Model Specific)

335

**Dia of Light
In (mm)**

**>140
lm/w**

Efficiency

1

LED Panel

**45
KGS**

Weight
(Model Specific)



Free from UV Interference. Multiple Circuits to Avoid Complete Run- Down

Specifications

Type of lamp/ Wattage	: LED/(Available in 150W / 200W / 250W / 300W)	Range (Up to)	: 150 w - 400m, 200 w - 600m 250 w - 800m, 300 w - 1000m
Available Models	: YK REVO 150 SR YK REVO 200 SR YK REVO 250 SR YK REVO 300 SR	Cordless Remote	: Features Include: ON - OFF Start/Stop Rotation - Optional Clockwise Rotation - Optional Anticlockwise Rotation - Optional Control Panel Board - Optional Inc. / Dec. RPM Speed - Optional
Efficiency	: >140 lm/w	Remote Range	: Up to 50M Line of Sight
Input Voltage	: 230v AC	LED life time	: 1,00,000 hours (Approx)
Working Voltage	: 100-300 Vac , 50Hz	Movement	: Clockwise Horizontal Auto Revolving Anticlockwise - Optional 360 Degree Vertical - 45 Degree (Manual)
Protection Against	: Over/Under Volts	Working Temp.	: -10 to +55 Degree C
Motor wattage	: 100W in Each Variant	Net Weight	: 150 SR-30 KGS , 200 SR-33 KGS, 250 SR-36 KGS , 300 SR-39 KGS
Revolving RPM	: 1.5 Can Be Customised from 1 to 10	Motor Dim	: 440 (L) x 370 (B) x 545 (H) mm
Color Temperature	: 6500K		
Beam angle	: 5° / Can be Customized for Higher Degrees		
IP Rating	: IP66		
Body Material	: Die Cast LM6 Body with Air Fins , Powder Coated		
Base	: Auto Revolving Mechanism (Customisation)		
Lens material	: Optical Grade PMMA- PC Lens		
Reflector Lens	: >90%		
Efficiency	: >140 Lm/W		
Glass	: Toughened Sealed with silicon Gasket		
Cordless Remote	: Optionally Available (Range Upto 50 Mtrs Open Area)		

(Specifications, Size, Shape, Colour, Appearance etc are subject to change without any notice at any stage, E. & O. E.)
pointblank.in